

## actiTape LTO Professional Line

LTO SAS Tape Drive in an 1U Rackmount Chassis  
or in an External Enclosure



### Product Highlights

- ✔ Robust in 1U Rackmount Chassis or external Enclosure (Tabletop)
- ✔ Built-in Power Supply Unit incl. separate ON/OFF switch
- ✔ Proven LTO-9 / LTO-8 technology with SAS Interface
- ✔ Up to 18TB Capacity (compressed up to 45TB\* per Data Cartridge)
- ✔ Up to 300 MB/s native data transfer rate (compressed up to 750MB/s\*)
- ✔ Connection to a centralized server via one external 6G or 12G SAS Interface supported for most popular backup and archive management software
- ✔ 36 Months limited warranty
- ✔ 36 Months exchange in advance Service (Fast Exchange Service)

### Linear Tape Open – LTO Tape Technologie

LTO technology has established itself as a State-of-the-art standard in the data backup and archiving market segment. With a LTO-9 capacity per Medium of 18-45\* TB and a data recording speed of up to 300-750\* MB/s, the vast majority of requirements for an exchangeable medium in small and medium-sized IT environments are met.

### Make saving Mission Critical Data easy

The actiTape LTO 1U or External Professional is easily connectable to an existing server via a SAS interface and will be operated by a server based backup or archive software. Loading and unloading of LTO media can be done easily by man. This allows mission-critical data to be stored on an exchangeable medium and kept securely at an external location.

### Service & Support included

actiCare service stands for a 36-month limited warranty including the proven Fast Exchange Service (Advance Replacement of defective parts) as well as free technical support by phone, e-mail and internet in English.

\* 2,5 : 1 Data Compression inline with LTO Standard



## acti Tape LTO Professional

LTO Tape Drive connected to an centralized server

The external acti Tape LTO Tape Drive has its own built-in power supply unit. The data are carried out via a powerful SAS interface, depend on model where an SFF-8088 or SFF8644 connector is equipped. Based on the SAS Host Bus Adapter (HBA), the SAS data cable must be selected correctly matching the server's interface. Today's SAS HBAs are usually equipped with external connectors according to the 6G SFF-8088 or the 12G SFF-8644 standard.

**Note:**

The acti Tape LTO External Professional delivery scope does not include an SAS data cable. However, these are available as options in the SFF-8088 to SFF-8088 and SFF-8088 to SFF-8644 variants.



## acti Tape LTO Professional

Selection of Backup or Archive Software

The operation of the acti Tape LTO Professional Drives (Tape Drives) requires backup or archiving software, which must be selected according to the requirements and installed on the server.

The backup or archiving software manages data on LTO media. Usually, the table of contents of the used media are also available in software's data bases, which allows a quick retrieval.

**Tipp:**


The manual, unique labelling by the user of LTO media protect for media mismatch. Labels beside the LTO media contents are very helpful.

## Backup and Archive Software with acti Tape LTO Professional Line


Most known Software Manufacturer with professional applications support the acti Tape LTO Professional Line. As examples:



## acti Tape LTO External Professional: (only LTO-8)



## acti Tape LTO 1U Professional:



## Compatibility LTO Recording Standard:

|             |              | LTO Technology |       |       |       |       |       |       |       |       |
|-------------|--------------|----------------|-------|-------|-------|-------|-------|-------|-------|-------|
|             |              | LTO-9          | LTO-8 | LTO-7 | LTO-6 | LTO-5 | LTO-4 | LTO-3 | LTO-2 | LTO-1 |
| LTO Media   | LTO-9        | R/W            | -     | -     | -     | -     | -     | -     | -     | -     |
|             | LTO-8        | R/W            | R/W   | -     | -     | -     | -     | -     | -     | -     |
|             | LTO-7 Type M | -              | R/W   | -     | -     | -     | -     | -     | -     | -     |
|             | LTO-7        | -              | R/W   | R/W   | -     | -     | -     | -     | -     | -     |
|             | LTO-6        | -              | -     | R/W   | R/W   | -     | -     | -     | -     | -     |
|             | LTO-5        | -              | -     | R     | R/W   | R/W   | -     | -     | -     | -     |
|             | LTO-4        | -              | -     | -     | R     | R/W   | R/W   | -     | -     | -     |
|             | LTO-3        | -              | -     | -     | -     | R     | R/W   | R/W   | -     | -     |
|             | LTO-2        | -              | -     | -     | -     | -     | R     | R/W   | R/W   | -     |
|             | LTO-1        | -              | -     | -     | -     | -     | -     | R     | R/W   | R/W   |
| CC-Cleaning |              | yes            | yes   | yes   | yes   | yes   | yes   | yes   | yes   | yes   |

Status: October 2021 / R = Read compatible / W = Write compatible  
- = LTO-Format is not supported

# acti Tape LTO Professional Line

## Technical Data

| Product Type                           | acti Tape LTO-8<br>External Professional   | acti Tape LTO-8 / LTO-9<br>IU Professional   |
|--|--|--|
| <b>Description</b>                     | LTO Tape Drive (HH half high)<br>in external Enclosure (Tabletop)  | LTO Tape Drive (HH half high)<br>in IU Rackmount / Chassis   |
| <b>Application</b>                     | LTO Backup Tape Drive for connection to a server via SAS interface   |  |
| <b>Recording Technology</b>            | LTO-8  | LTO-9 / LTO-8<br>Depending on type of Tape Drive   |
| <b>Capacity<br/>native/compressed*</b> | LTO-8: 12TB / 30TB*  | LTO-8: 12TB / 30TB*<br>LTO-9: 18TB / 45TB*   |
| <b>Compatibility<br/>Write/Read</b>    | LTO-8: Write LTO-8 / LTO-7;<br>Read LTO-8 / LTO-7  | LTO-8: Write LTO-8 / LTO-7;<br>Read LTO-8 / LTO-7<br>LTO-9: Write LTO-9 / LTO-8;<br>Read LTO-9 / LTO-8                                   |
| <b>Interface</b>                       | Serial SCSI (SAS) – SFF-8088<br>external connector   | Serial SCSI (SAS) – SFF-8088 or SFF-8644<br>external connector   |
| <b>Power Supply Unit</b>               | 110-240 Volt<br>50W  | 110-240 Volt<br>350W   |
| <b>Power Consumption (typ.)</b>        | ca. 34W  | ca. 35W  |
| <b>Operation Conditions</b>            | Temperature: 10-35°C (Operation)<br>-10°C - 50°C (Transportation)<br>Humidity (not condensed): 20-50%<br>(recommended with change <5%/h) | Temperature: 10-27°C (Operation)<br>-10°C - 50°C (Transportation)<br>Humidity (not condensed): 20-50%<br>(recommended with change <5%/h) |
| <b>Dimension<br/>Weight</b>            | 98 x 59 x 259 mm (W x H x D)<br>ca. 3,8kg  | 480 x 44,5 x 585 mm (W x H x D)<br>ca. 7,4kg   |
| <b>Limited Warranty</b>                | 36 Months (3 Years) incl. Fast Exchange Service (FESc)<br>E-Mail/Internet-Support & Telephone Hotline                                    |  |
| <b>Certification</b>                   | CE, TÜV-Safety, RoHS   |  |
| <b>Optional Accessories</b>            | LTO Cleaning Cartridge, LTO Data Cartridge (Medium)<br>SAS Cable, SAS Host Bus Adapter<br>Telescope-Rails (for IU Version only)          |  |

\* 2,5 : 1 Data Compression inline with LTO Standard

# acti Tape LTO Professional Line

## Product Configurations:

| Item No.    | Product Configuration: acti Tape LTO Professional Line                     |
|-------------|--|
| I8202000 ** | acti Tape LTO-8 external professional (extern Tabletop), SAS 6G (SFF-8088) |
| I8402000    | acti Tape LTO-8 IU professional (extern Rackmount), SAS 6G (SFF-8088)      |
| I9402000    | acti Tape LTO-9 IU professional (extern Rackmount), SAS 12G (SFF-8644)     |

\* EOL planned in 2025 – check for availability