



EonStor GSe U.2 NVMe All-Flash Storage

Scale-out Unified Storage for SMB

Highlights

High Performance

- Up to 600K IOPS to accelerate storage operations
- Massive sequential throughput of up to 12GB/s read and 9GB/s write

Cost-Effective Storage

- U.2 NVMe SSD to deliver better performance at lower costs
- Automated storage tiering to fully utilize SSD and HDD

Flexible Scalability

- Scale-out and scale-up expansions to easily expand performance and capacity

Easy to Use and Manage

- Single namespace for easier data access
- Auto-balancing to reduce the burden of storage management for IT staff

Introduction

EonStor GSe U.2 NVMe all-flash storage is a high performance unified storage solution with a single controller designed for SMB. Equipped with U.2 NVMe SSDs, it delivers high IOPS and throughput at a cost-effective price. This series supports both SAN and NAS services, provides block-level and file-level scale-out expansions to linearly increase performance and capacity, and comes with complete enterprise-grade data protection features that allow IT staff to focus on higher value projects. It thus makes a perfect fit for applications such as database, virtualization, M&E, file sharing, and backup.

End-to-End High Performance with U.2 NVMe SSD

Supporting PCIe 4.0, NVMe U.2 SSD, and 100GbE connectivity with RDMA, GSe U.2 NVMe storage delivers a higher speed with a lower latency, providing up to 12GB/s read and 9GB/s write in throughput and 600K on a single appliance.

Cost-Effectiveness and High Storage Efficiency

U.2 NVMe SSD is becoming the mainstream in the market as it combines the advantages of SAS and SATA SSDs, allowing enterprises to enjoy higher performance at a competitive price.

EonStor GSe U.2 NVMe storage supports hybrid storage, and with automated storage tiering, the storage system can automatically leverage the high throughput and low latency of U.2 NVMe SSDs for frequently accessed data, while using HDDs on expansion enclosures as data backup media, thereby boosting system performance at a reduced total cost of ownership.

EonStor GSe U.2 NVMe storage also comes with inline compression and offline deduplication, which reduces the storage capacity required and thus saves storage costs. The inline compression feature compresses raw files in real-time, which greatly reduces the data size and the transfer time. To deal with repeated files saved by manual backups or archiving, offline deduplication helps you automatically remove duplicate data from a cluster to free up storage space.

Flexible Scalability with Scale-out and Scale-up

Through scale-out expansion, you can linearly increase performance and capacity for both block-level and file-level data. When one storage appliance is no longer able to provide enough performance or capacity, you can simply add more appliances to form a cluster—with a maximum of 4 appliances.

Through scale-up expansion, each storage appliance can be connected to JBOD expansion enclosures to add up to 896 drives. Together with scale-out expansion, GSe U.2 NVMe storage supports more than 3000 drives with over 70PB storage capacity.

Easy Data Access and Simple IT Management

Users can access shared folders in a single root directory under a single namespace, so that they don't need to worry about where the data is placed. Auto-balancing is also supported to achieve the benefit of load balancing without the burden of manual IT planning and configuration.

Smart Management for SSD

EonStor GSe U.2 NVMe storage uses an intelligent algorithm to handle data writes and optimize SSD usage. The algorithm not only extends SSD lifespan by reducing the total amount of writes on an SSD but also prevents multiple SSDs from failing at the time and causing data loss. In addition, as EonStor GSe U.2 NVMe storage monitors SSD status in real time, it estimates the remaining lifespan of each SSD and sends the administrator a reminder to replace the SSD that is about to fail.

Essential Applications Designed for SMBs

EonStor GSe U.2 NVMe storage also comes with essential office applications for small and medium-sized businesses, such as email servers and office document software. Setting up and activating these applications can be completed with just a few clicks, even by those without a technical background. This greatly simplifies the tedious process of installing and configuring office-related software, thus saving time.

Complete Data Protection and Backup

EonStor GSe U.2 NVMe storage offers various data protection mechanisms to guarantee data safety. First, Infortrend's unique RAID technology ensures your data remains intact even in case of a drive failure. With snapshot, a flexible backup tool, you can back up local resources on a storage system by schedule, including volumes and shared folders, and roll back to a previous version when needed. For further protection, you can back up data to a remote GSe appliance using the remote replication feature, or to a public cloud with EonCloud Gateway.

Immutable object storage, another crucial feature for data protection, safeguards data against ransomware attacks. It retains data with WORM (write once read many) storage protection, where data gets "locked" and therefore cannot be modified, deleted, overwritten, or even encrypted by ransomware. By setting a retention period, you can easily follow government compliance requirements or company policies on data retention.

For companies requiring an easy-to-use and reliable storage solution for file backup, EonStor GSe U.2 NVMe storage can be utilized as a backup appliance, allowing you to leverage its backup service to back up PC folders, file servers, and public cloud through a GUI interface. Additionally, you can set options such as a backup schedule and a retention period to best fit your needs.

Availability and Reliability

EonStor GSe U.2 NVMe storage is equipped with dual power supplies and cooling fans to help ensure high data availability. The Cache Backup Module (CBM) consists of a super capacitor and a flash module to prevent data loss during a power interruption or outage.

In addition, EonStor GSe U.2 NVMe storage offers HA service to deliver continuous availability with a near zero RTO (recovery time objective) and a zero RPO (recovery point objective). With two storage devices deployed at near sites, the HA service provides block-level active-active storage and file-level active-passive storage for business-critical applications that have an extremely low tolerance for downtime. Featuring synchronous remote replication and auto-failover, this solution ensures identical and complete copies of data are stored on both storage devices and avoids service downtime due to planned or unexpected events. Auto-failback is available in block-level HA service, allowing a storage device to resume services without switching manually.

Intuitive Management Software

EonStor GSe U.2 NVMe storage adopts EonOne, a web-based management software tool, to assist customers in raising storage and service efficiency for increased productivity. With its intuitive interface design, IT administrators can easily manage a cluster and multiple appliances, monitor performance and capacity usage, and complete system configurations, all from one centralized interface.

PHYSICAL SPECIFICATIONS

Product Series		GSe 2000U	GSe 3000U	GSe 3000UT	GSe 4000U
Form Factor	2U 24-bay	GSe 2024UR	GSe 3024UR	GSe 3024URT	GSe 4024UR
Note: U: NVMe storage R: Dual redundant controllers T: High performance					
Controller		Single			
Cache Backup Technology		Super capacitor + flash module (optional)			
CPU		Intel® Xeon® D 2-Core	Intel® Xeon® D 4-Core	Intel® Xeon® D 4-Core	Intel® Xeon® D 6-Core
Cache Memory		Default DDR4 8GB, up to 64GB	Default DDR4 8GB, up to 64GB	Default DDR4 12GB, up to 192GB	Default DDR4 12GB, up to 192GB
Supported Drives		2.5" U.2 NVMe SSD (must be purchased from Infortrend)			
Note: For the latest compatibility details, refer to our official website for the latest Compatibility Guide.					
Max. Drive Number	Via Expansion Enclosures, per Appliance	896	896	896	896
	Via Scale-out with Other Series of Appliances, per Cluster	3584	3584	3584	3584
Max. SSD Cache Pool (Block Level)		4TB	4TB	4TB	4TB
Onboard 10GbE Ports (SFP+)		0	2	0	0
Onboard 25GbE Ports (SFP28)		0	0	2	0
Max. Host Board Slots		2	2	2	2
Host Board Options		<ul style="list-style-type: none"> • 16Gb/s FC x 4 • 32Gb/s FC x 2 • 1GbE (RJ-45) x 4 • 10GbE (SFP+) x 2 • 25GbE (SFP28) x 2 • 12Gb/s SAS x 2 		<ul style="list-style-type: none"> • 16Gb/s FC x 4 • 32Gb/s FC x 2 • 32Gb/s FC x 4 • 10GbE (SFP+) x 2 • 25GbE (SFP28) x 2 • 100GbE (QSFP28) x 1, RDMA • 100GbE (QSFP28) x 2, RDMA • 12Gb/s SAS x 2 	
	Note: 1. One 100GbE x 2 host board delivers a maximum throughput of 100Gb/s. 2. At least 24GB memory is required per controller to use 100GbE RDMA. 3. It is strongly recommended that you refer to the latest Host Board and Memory Guide on our website for complete information, including supported combinations and important notes, before purchasing any host board for your model.				
Max. 16Gb/s FC Ports		8	8	8	8
Max. 32Gb/s FC Ports		8	8	8	8
Max. 10GbE Ports (SFP+)		4	4	4	4
Max. 25GbE Ports (SFP28)		4	4	4	4
Max. 100GbE Ports (QSFP28)		0	0	2	2
Max. 12Gb/s SAS Ports		4	4	4	4
Expansion Enclosures (JBODs)		JB 3012A, JB 3016A, JB 3024BA, JB 3025BA, JB 3060L, JB 3090			
Dimensions (Without Chassis Ears and Protrusions) (W x H x D)		449 x 88 x 500 mm		449 x 88 x 530 mm	
Package Dimensions (W x H x D)		780 x 338 x 588 mm			
Power Supply Unit	Power Supplies (Redundant and Hot-swappable)	Global	530W x 2 (80 PLUS Bronze)		
		EU	800W x 2 (80 PLUS Titanium)		
AC Voltage	Global	100VAC @10A to 240VAC @5A			
	EU	100-127VAC @10A, 200-240VAC @5A			
Frequency		50-60 Hz			
Safety Standards		<ul style="list-style-type: none"> • Electromagnetic compatibility: CE, BSMI, FCC • Safety: UL, BSMI, CB 			

SOFTWARE SPECIFICATIONS

Max. Logical Drive Number	30			
Max. Logical Drive Capacity	512TB			
Stripe Size (per Logical Drive)	16KB, 32KB, 64KB, 128KB, 256KB, 512KB, or 1024KB			
Write Policy (per Logical Drive)	Write-back or write-through			
Max. Pool Size	2PB			
Max. Pool Number	30			
Max. Volume Size	2PB			
Max. Volume Number	1024			
Max. Host LUN Mapping Number	4096			
Max. Reserved Tag Number (per Host-LUN Connection)	256			
Max. iSCSI Sessions	416			
Max. Host Connection Number (per FC)	128			
RAID Options	RAID 0, RAID 1, RAID 3, RAID 5/5F, RAID 6/6F, RAID 10, RAID 30, RAID 50, RAID 60			
Supported Protocols	File Level	CIFS/SMB (version 2.0/3.0), NFS (version 2/3/4), AFP (version 3.1.12), FTP/FXP (vsftp 2.3.4), WebDAV (httpd package 2.4.6)		
	Block Level	FC, iSCSI, SAS		
	Object Level	RESTful API		
File Level	Max. File System Size	2PB		
	Max. Number of User Accounts	20000		
	Max. Number of User Groups	512		
	Max. Number of Shared Folders	2048 (NFS/CIFS/FTP) 255 (AFP)		
	Max. Number of Rsync Jobs	1024		
	Max. Number of Concurrent Rsync Processes	64		
Management	Max. Number of Connections	2048 (NFS/CIFS/AFP) 1024 (FTP)		
		<ul style="list-style-type: none"> • Web-based EonOne management software • User account management • Group management • Folder management - folder access control • Quota management 	<ul style="list-style-type: none"> • Folder encryption with AES • Integration with Microsoft Active Directory (AD) and Linux LDAP • Storage Resource Management to analyze history of resource usage • Multi-factor authentication login mechanism • File-level QoS (network traffic control) 	
Availability and Reliability	<ul style="list-style-type: none"> • Immutable object storage • Hot-swappable hardware modules • Device mapper • Antivirus • Trunk group 	<ul style="list-style-type: none"> • Cache safe technology • UPS • WORM (file level only) • SMB Multichannel • Backup Service 		
Efficiency	<ul style="list-style-type: none"> • Inline compression 	<ul style="list-style-type: none"> • Offline deduplication 		
Notification	<ul style="list-style-type: none"> • Email 	<ul style="list-style-type: none"> • SNMP traps 		
Applications	M&E	<ul style="list-style-type: none"> • Project Server 	<ul style="list-style-type: none"> • ResouceSpace 	
	Data Backup	<ul style="list-style-type: none"> • Object Storage 		
	File Sharing and Syncing	<ul style="list-style-type: none"> • Nextcloud 		
	Productivity	<ul style="list-style-type: none"> • Mail Server 	<ul style="list-style-type: none"> • Web Server 	<ul style="list-style-type: none"> • ONLYOFFICE
	Management	<ul style="list-style-type: none"> • Proxy Server 	<ul style="list-style-type: none"> • LDAP Server 	<ul style="list-style-type: none"> • Syslog Server • VPN Server
	Security	<ul style="list-style-type: none"> • Anti-virus 		
Utility	<ul style="list-style-type: none"> • File Explorer 	<ul style="list-style-type: none"> • Docker 		
Supported Cloud Services	EonCloud Gateway supports integration with the following cloud providers: Amazon S3, Microsoft Azure, Alibaba Cloud, OpenStack, Baidu Cloud, Google Cloud, Tencent Cloud, Wasabi Cloud, etc.			
	Note: For complete information about cloud provides support, please refer to EonCloud Gateway webpage https://www.infortrend.com/global/solutions/eoncloud			
Supported OS	Microsoft Windows Server, Red Hat Enterprise Linux, SUSE Linux Enterprise, Sun Solaris, macOS X, VMware			
	Note: For supported OS versions, please refer to the Compatibility Guide.			

DATA SERVICES

Thin Provisioning	Block Level	Default	"Just-in-time" capacity allocation optimizes storage utilization and eliminates allocated but unused storage space.		
Local Replication	Snapshot	File Level	Optional		
		Block Level	Default	Snapshot images per source partition: 1024	
	Volume Copy/Mirror	Block Level	Default	Snapshot images per source partition: 64	Snapshot images per pool: 128
		Block Level	Optional	Snapshot images per source partition: 256	Snapshot images per pool: 4096
	Block Level	Default	Replication pairs per source volume: 4	Replication pairs per system: 16	
Block Level	Optional	Replication pairs per source volume: 8	Replication pairs per system: 256		
Remote Replication	File Level	Default	Support Rsync with 128-bit SSH encryption		
	Block Level	Optional	Replication pairs per source volume: 8	Replication pairs per system: 64	
			Note: The maximum number of replication pairs per source volume is 8, whether they are remote asynchronous pairs, remote synchronous pairs, or local volume pairs		
Automated Storage Tiering		Optional	Storage tiers per pool: 4		
Scale-out	File Level	Default	Appliances per cluster: 1		
		Optional	Appliances per cluster: 4		
	Block Level	Default	Appliances per cluster: 4		
HA Service	File Level	Optional	Delivering continuous availability and eliminating downtime for mission-critical workloads that require non-stop operations		
	Block Level		Note: HA Service is not available on GSe 2000U.		
SSD Cache	File Level	Optional	Accelerating file operations and data access performance for both read and write Max. SSD number: 8		
	Block Level	Optional	Accelerating data access in random read-intensive environments (e.g. OLTP) Max. SSD number: 4		
			Recommended DIMM capacity per controller for SSD cache pool		
			DRAM: 8GB	Max SSD cache pool size: 0.5TB	
			DRAM: 16GB	Max SSD cache pool size: 1TB	
			DRAM: 32GB	Max SSD cache pool size: 2TB	
DRAM: 64GB and up	Max SSD cache pool size: 4TB				

WARRANTY AND SERVICE

	Standard Service	3-year limited hardware warranty and 8x5 phone, web, and email support (batteries are covered under warranty for 2 years)
Service and Support	Upgrade or Extension Options	<p>Warranty extension: Standard service can be extended up to 5 years. The following service can be upgraded to 5 years.</p> <ul style="list-style-type: none"> • Upgrade: Replacement part dispatch on the next business day • Advanced service: 24x7 phone, web, and email support + onsite diagnostics on the next business day • Premium service: 24x7 phone, web, and email support + onsite diagnostics in 4 hours <p>Note: Options may vary by region. For more details, please contact our sales representatives.</p>
	Technical Support	Get information on system installation and maintenance, download technical documents and software, or issue a support ticket
	Product Services	Register products, download firmware, apply for licensing services, create product repair tickets, or check product repair status

Asia Pacific (Taipei, Taiwan)
Infotrend Technology, Inc.
Tel : +886-2-2226-0126
E-mail : sales.ap@infotrend.com

China (Beijing, China)
Infotrend Technology, Ltd.
Tel : +86-10-6310-6168
E-mail : sales.cn@infotrend.com

Japan (Tokyo, Japan)
Infotrend Japan, Inc.
Tel : +81-3-5730-6551
E-mail : sales.jp@infotrend.com

Americas (Sunnyvale, CA, USA)
Infotrend Corporation
Tel : +1-408-988-5088
E-mail : sales.us@infotrend.com

EMEA (Basingstoke, UK)
Infotrend Europe Ltd.
Tel : +44(0)-1256-305-220
E-mail : sales.eu@infotrend.com

